#####################
######################ÿ□#ÿÿd#########U#########q##□##Xö□#O
P#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########□###□ Coordinated through the BDE S4 or directly with Spt Ops for non BDE units.##□ Pushed to BSA by the MSB and/or throughput from COSCOM.#

```
#□#########□#########
      #######□#########□####ÿ□#ÿÿd#########U#########q##□##□#□ÿĐ
      Ü#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########x###□ Bulk fuel requirements are
based on:#  □ Forecasts from customer units#  □ Equipment densities#  □ Daily
usage reports
```

```
############################################ÿ□#ÿÿd#########U#########q##□##Ëõ¿ú#
###ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########□###□ Forecasts are submitted on unit
LOGSTAT Reports.##□ Forecasts are planning tools.  Spt Ops finalizes requests
for #bulk fuel to DISCOM Spt Ops 24 hours out.##□ Spt Ops officers may establish
a standard "push" requirement #based on past consumption and storage
capabilities##□ Forecasts, receipts and issues must be tied to the tactical
#mission.  Synchronization of issues with receipts is critical.
```

```
°ÿ#
³ÿ#
¶ÿ
¹ÿ!
¼ÿ"
Àÿ"
Ãÿ#
Æÿ#####
ÎÿJ
##J
ÐÿH
ÚÿF
âÿE
èÿB
ðÿ@
öÿ<
ýÿ8
###
áÿ#
âÿ#
ßÿ
Üÿ!
Ùÿ"
Öÿ"
Òÿ%
ÎÿH###ê   ÿ#
æÿ#
Êÿ#
Çÿ#
Åÿ#
Âÿ#
Àÿ#
¾ÿ#
¼ÿ#
¹ÿ#
¸ÿ#
¶ÿ#
´ÿ#
²ÿ#
±ÿ#
°ÿ

¯ÿ#
®ÿ#
®ÿ#
®ÿ#
ÿ#
®ÿý ®ÿü ®ÿú ¯ÿø °ÿö ±ÿô ²ÿò ´ÿñ ¶ÿð ¸ÿî ¹ÿí ¼ÿì ¾ÿì Àÿë
    Âÿê Åÿê Çÿê Êÿê Ìÿê Îÿë Ñÿì Óÿì Õÿí Øÿî Úÿð Üÿñ Þÿò
    ßÿô áÿö âÿø ãÿú äÿü åÿý åÿ#
æÿ#
æÿ#
æÿ#
åÿ#
åÿ

äÿ#
ãÿ#
âÿ#
áÿ#
ßÿ#
Þÿ#
```

```
Éÿ#
Èÿ#
Çÿ#
Æÿ#
Åÿ

Äÿ

Ãÿ
Âÿ#
Áÿ#
Àÿ#
Àÿ#
Àÿ#
¿ÿ#
¿ÿ#
¿ÿ#
Àÿ#
Àÿÿ   Àÿþ   Áÿý   Âÿü   Ãÿü   Äÿû   Åÿû   Æÿû   Çÿú   Èÿú   Éÿú   Êÿú   Ìÿû   Ìÿû
      Íÿû   Îÿü   Ïÿü   Ðÿý   Ñÿþ   Òÿÿ   Òÿ#
Óÿ#
Ôÿ#
Ôÿ#
Ôÿ#
Ôÿ#
Ôÿ#
Óÿ#
Óÿ#
Òÿ#
Òÿ
Ñÿ

Ðÿ

Ïÿ#
Îÿ#
Íÿ#
Ìÿ
```

```
#####################
######################ÿ□#ÿÿd#########U#########q##□##æõ□üÀý¹ýÿÿ####ÿÿ#####ÿ□#ÿÿd
#########U#########.###o Supply Company establishes #point in the BSA
```

#####################
######################ÿ□#ÿÿd#########U#########q##□##æõt#Øüª#ÿÿ####ÿÿ#####ÿ□#ÿÿd
#########U#########,###o Best used when distances #are not a factor

#,#########,################,#########,####ÿ□#ÿÿd#########U#########q##□##ï#□üì
¾ýÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########B###o Reduces TAT for BDE fuelers
by #pushing fuel closer to CBT units

```
#B#########B################B#########B####ÿ□#ÿÿd#########U#########q##□##ï#ýþP
      3#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########=###o Performed using FSB assets
or #throughput from MSB or Corps#
```

```
#,#########,#########
#######,#########,####ÿ□#ÿÿd#########U#########q##□##□õ1ýc#Ìýÿÿ####ÿÿ#####ÿ□#ÿÿd
#########U#########2###o Synonymous with rapid or hot refuel for aircraft
```

#2#########2#########
#######2#########2####ÿ□#ÿÿd#########U#########q##□##²õëþë#!
#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########]###o Any number of equipment
configurations and #options are available to accomplish the mission#

####ÿ□#ÿÿd#########U#########q##□###õ#ü¼þÄ#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########□###□ BDE S4 coordinates ROM, #preferably 48-72 hours in advance.##□ ROMs are not usually conducted #when:# - Within range of enemy cannon arty# - Unit is in tactical formations##□ Route recon should be conducted to #determine trafficability, staging, #traffic control, and concealment #requirements.##□ BDE S4 should provide march #tables, fuel forecasts, call signs/freqs, #vehicle densities, etc.#

```
###########################################ÿ□#ÿÿd#########U#########q##□##"#F#

##ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########T###o Tanker resupply is critical.  SPO
#must coordinate resupply after #ROM is complete
```

øÖú ø□ú ø□ú ø□ú ø□ú ø□ú ø□ú
ø□ú
ø□ú
ø□ú
ø□ú
ø□ú
ø□ú
ø□ú
ø□ú
ø□ú#ø□ú#ø□ú#ø□ú#ø□ú#ø□ú#ø□ú

###ÿ□#ÿÿd#########U#########q##□##¢õÇý¯
Ó#ÿÿ####ÿÿ#####ÿ□#ÿÿd#########U#########÷###□ Bulk fuel requirements are estimates based on forecasts from customer units #   and based on densities, usage, and fuel type.##□ Supply point best used when distances aren't a factor.##□ ROM execution is based on time not gallons; used to enhance TF CBT power   and momentum. ROM operations employ a variety of equipment configurations. ##□ LRP and ROM Ops require extensive prior coordination with customers and # DISCOM/CSB. The Spt Opns must understand the flow of bulk fuel within the corps.#

```
############################################ÿ#ÿÿd#########d#########r####ªö-ùV
      Ãûÿÿ,###ÿÿ#####ÿ#ÿÿd#########d######### ###Click to edit Master title
style
```